

Komponenter Lyrschacklar

Höghållfasta, smidda schacklar


Enl. U.S. Specifikation RR-C-271

Får ej värmebehandlas

Märkta med max last


Säkerhetsfaktor 6:1

Ytbehandling: galvaniserad med målad skruv



Artikel nr	Dimensioner mm*						Max last ton	Vikt kg
	d	d1	a	c	d2	e		
90550500	6	8	12	29	16	20	0,5	0,06
90550501	8	10	13	32	20	21	0,75	0,11
90550502	9	11	16	36	22	26	1,0	0,15
90550503	11	13	18	43	26	29	1,5	0,21
90550504	13	16	21	47	33	33	2,0	0,37
90550505	16	19	27	60	40	42	3,25	0,65
90550506	19	22	31	71	47	51	4,75	1,1
90550507	22	25	37	84	50	58	6,5	1,5
90550508	25	28	43	95	58	68	8,5	2,2
90550509	28	32	46	108	64	74	9,5	3,1
90550510	32	35	52	119	72	83	12,0	4,2
90550511	35	38	57	132	74	89	13,5	6,0
90550512	38	42	60	146	84	98	17,0	8,0
90550513	45	50	74	178	105	127	25,0	13,5
90550514	50	57	83	197	127	138	35,0	19,0
90550515	65	70	105	255	152	185	55,0	38,0

* Tolerans +- 5% för mått a + c



90550600	6	8	12	29	16	20	0,5	0,07
90550601	8	10	13	32	20	21	0,75	0,13
90550602	9	11	16	36	22	26	1,0	0,17
90550603	11	13	18	43	26	29	1,5	0,25
90550604	13	16	21	47	33	33	2,0	0,42
90550605	16	19	27	60	40	42	3,25	0,7
90550606	19	22	31	71	47	51	4,75	1,2
90550607	22	25	37	84	50	58	6,5	1,7
90550608	25	28	43	95	58	68	8,5	2,5
90550609	28	30	46	108	64	74	9,5	3,4
90550610	32	35	52	119	72	83	12,0	4,8
90550611	35	38	57	132	74	89	13,5	7,0
90550612	38	42	60	146	84	98	17,0	9,0
90550613	45	50	74	178	105	127	25,0	15,0
90550614	50	57	83	197	127	138	35,0	21,0
90550615	65	70	105	255	152	185	55,0	41,0
90550616	75	80	127	330	165	190	85,0	62,0
90550617	89	95	146	380	203	235	120,0	110,0

* Tolerans +- 5% för mått a + c