



## Komponenter Raka Schacklar

Höghållfasta, smidda schacklar  
Enl. U.S. Specifikation RR-C-271  
Får ej värmebehandlas  
Märkta med max last  
Säkerhetsfaktor 6:1  
Ytbehandling: galvaniserad med målad skruv



Artikel nr	Dimensioner mm*					Max last ton	Vikt
	d	d1	a	c	d2		
90560500	7	8	12	25	12	0,5	0,06
90560501	9	10	13,5	27	16	0,75	0,11
90560502	10	11	17	31	20	1,0	0,15
90560503	11	12	18,5	37	22	1,5	0,21
90560504	13	16	21	41	33	2,0	0,25
90560505	16	19	27	51	40	3,25	0,55
90560506	19	22	31	60	47	4,75	1,0
90560507	22	25	37	71	50	6,5	1,3
90560508	25	28	43	81	58	8,5	1,9
90560509	28	32	46	90	64	9,5	2,8
90560510	32	35	52	100	72	12	3,6
90560511	35	38	57	111	74	13,5	4,6
90560512	38	42	60	122	84	17	6,5
90560513	45	50	74	149	105	25	11,5
90560514	50	57	83	171	127	35	16,0

\* Tolerans +- 5% för mått a + c



90560604	13	16	21	41	33	2,0	0,3
90560605	16	19	27	51	40	3,25	0,6
90560606	19	22	31	60	47	4,75	1,1
90560607	22	25	37	71	50	6,5	1,5
90560608	25	28	43	81	58	8,5	2,2
90560609	28	32	46	90	64	9,5	3,1
90560610	32	35	52	100	72	12	4,2
90560611	35	38	57	111	74	13,5	5,6
90560612	38	42	60	122	84	17	7,5
90560613	45	50	74	149	105	25	13,0
90560614	50	57	83	171	127	35	18,0
90560615	65	70	105	203	152	55	

\* Tolerans +- 5% för mått a + c