



Ställina förzinkad

Formlagd högerslagen	Artikel nr	LinØmm	Min brottlast kp 160-180 kp/mm ²	Vikt kg/100m
----------------------	------------	--------	--	--------------

6x4+FC

Ej för lyft

S181001

1

67


0,99

S181015

1,5

98

1,1



4x3+FC


Ej för lyft

S190001

1

67

0,99



1x19+Fc


Ej för lyft

S221615

1,5

213

1,1



6x7+FC

Ej för lyft

S231002

2

240

1

S231015

2,5

310

2,3

S231003

3

540

3,25

S231004

4

960

5

S231005

5

1500


8,95

S231006

6

2150

13



7x7+IWRC

Ej för lyft

S221515

1,5

250

1,1

S221518

1,8

325

1,15

S221523

2,3

400

2,1

S221525

2,5

450

2,3

S221503

3

500

3,1

S221540

4

1000


6,1

S221560

6





2200

13





Stållina förzinkad

Formlagd högerslagen	Artikel nr	LinØmm	Min brottlast kp 160-180 kp/mm ²	Vikt kg/100m
6x12+7FC Ej för lyft 	S151003	3	301	2,26
	S151004	4	534	4,01
	S151005	5	835	6,27
	S151006	6	1200	9,02
	S151008	8	2140	16
	S151012	12	4810	36,1
	S151013	13	5640	42,4
	S151016	16	8550	64,2
6x19+FC 	S161003	3	499	3,11
	S161004	4	887	5,54
	S161005	5	1390	8,65
	S161006	6	2000	12,5
	S161008	8	3550	22,1
	S161010	10	5550	34,6
	S161012	12	7990	49,8
	S161013	13	9370	58,5
S161016	16	14200	88,6	
6x24+7FC 	S201005	5	1260	9,5
	S201006	6	1610	11,5
	S201008	8	2870	20,4
	S201010	10	4490	31,8
	S201012	12	6460	45,8
	S201013	13	7580	53,8
	S201014	14	8790	62,4
	S201016	16	11500	81,5
	S201018	18	14500	103
	S201020	20	17900	127
	S201022	22	21700	154
	S201024	24	25800	183
S201026	26	30300	215	
7x19 Aircraft 	S211003	3	910	3,9
	S211004	4	1270	6,9
	S211005	5	1910	9,5
	S211006	6	3180	15,5
	S211008	8	4450	26
	S211009	9	6545	29
	S211010	10	6970	34,6



Stållina förzinkad

Formlagd
högerslagen

Artikel nr


LinØmm

Min brottlast kp
160-180 kp/mm²

vikt kg/100m


6x36WS+IWRC

Ej för lyft




S251108	8	5080	26,7
S251110	10	6430	41,8
S251112	12	9260	60,2
S251112	13	10900	70,7
S251114	14	12600	82
S251116	16	16500	107
S251118	18	20800	135
S251120	20	25700	167
S251122	22	31100	202
S251124	24	37000	241
S251126	26	43500	283
S251132	32	65900	428
S251136	36	83300	542

6x36WS+FC



S251008	8	4100	24,3
S251010	10	5950	38
S252012	12	8570	54,7
S251013	13	10100	64,3
S251014	14	11700	74,5
S251016	16	15200	97,5
S251018	18	19300	123
S251020	20	23800	152
S251022	22	28800	184
S251024	24	34300	219
S251026	26	40300	257
S251028	28	46700	298
S251032	32	61000	386


6x37+FC



S251206	6	1910	12,5
S251208	8	3400	22,1
S251210	10	5310	34,6
S251212	12	7640	49,8
S251214	14	10400	67,8
S251216	16	13600	88,6

18x7

Rotationsfri




S451005	5	1480	10
S451006	6	2130	14,5
S451007	7	2900	19,7
S451008	8	3790	25,7
S451009	9	4800	32,6
S451010	10	5920	40,2
S451012	12	7170	57,9
S451014	14	11600	78,8
S451016	16	15200	103




Stållina förzinkad PVC-belagd


Formlagd högerslagen	Artikel nr	LinØmm	Min brottlast kp 160-180kp/mm ²	Vikt kg/100m
6x7+FC Ej för lyft	S171113	1,3-2,3	110	0,99
	S171123	2-3	270	2,1
	S171125	2,5-5	310	3,15
	S171134	3-4	490	4,07
	S171135	3-5	539	5,2
	S171144	4-5	1070	6,7
	S171146	4-6	959	7,9
	S171156	5-6	1600	9
S171168	6-8	2152	9,4	



6x7+FC Röd PVC Ej för lyft	S171034	3-4	490	4,07
	S171035	3-5	539	5,2




6x19+FC	S171246	4-6	887	15,5
	S171268	6-8	2000	18,12
	S171281	8-10	3580	23
	S171312	10-12	6040	35






Stållina blank oljad


Formlagd högerslagen	Artikel nr	LinØmm	Min brottlast kp 160-180kp/mm2	Vikt kg/100m
6x19+FC Ej för lyft	S201216 S201218	16 18	14200 21300	75 112



8x19+IWRC Ej för lyft	S291008	8	2810	24,5
---------------------------------	---------	---	------	------



6x12+FC	S151108 S151116	8 16	2140 8550	16 64,2
----------------	--------------------	---------	--------------	------------






Stållina Rostfri

Formlagd högerslagen


7x19



Artikel nr	LinØmm	Min brottlast kp 160-180kp/mm ²	Vikt kg/100m
S221002	2	215	1,7
S221025	2,5	340	2,4
S221003	3	600	3,8
S221004	4	950	6
S221005	5	1400	8,6
S221006	6	2100	13,5
S221008	8	3800	24
S221010	10	6000	37,5
S221012	12	8600	64
S221014	14	9700	60
S221016	16	13570	63


1x19

Ej för lyft




S221101	1	84	0,99
S221115	1,5	189	1,2
S221102	2	340	2
S221125	2,5	550	3,1
S221103	3	750	4,5
S221104	4	1400	7,9
S221105	5	2100	12,4
S221106	6	3000	17,8
S221107	7	4100	24,3
S221108	8	5400	31,7
S221110	10	6900	49,4
S221112	12	8600	74,3

7x7



S221210	1	57	0,41
S221312	1,2	92	0,6
S221215	1,5	145	0,99
S221220	2	230	1,4
S221325	2,5	380	2,7
S221330	3	500	3,1
S221240	4	1000	6,1
S221306	6	2200	13,3
S221308	8	4100	24,6

6x36+IWRC



S1611110	10	5760	38
----------	----	------	----



Stållina Rostfri PVC-belagd

Formlagd högerslagen	Artikel nr	LinØmm	Min brottlast kp 160-180kp/mm2	Vikt kg/100m
-------------------------	------------	--------	-----------------------------------	--------------


7x19

S221446

4-6

960

9



7x7

S170886

4-6

1000

9

S170847

4-8

1000


11

S170858

5-8

1600

15



1x19

S170946

4-6

1400

11,21

S170947

4-8

1400

12,45

S170958

5-8

2100

16

